

2Fast™



COVERSTOCK: R2S™ Pearl Reactive

WEIGHT BLOCK: N.O.S.™ Core

FACTORY FINISH: 1500-grit Polish

BALL COLOR: Amethyst/Peridot

DUROMETER: 74-76 Rex D-scale

FLARE POTENTIAL: 4" - 5" (Medium-High)

FRAGRANCE: Grape

WEIGHTS: 10-16 lbs.

Lbs.	RG	Diff.
16	2.53	0.044
15	2.53	0.045
14	2.59	0.043
13	2.68	0.018
12	2.70	0.021

Resurfacing to a 1500-grit Polished Factory Finish

Resurface to the original factory finish using a ball spinner.

1. 500-grit Abralon® - Sand for 30 seconds on all four sides with firm pressure.
2. 1000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
3. 2000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
4. 4000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
5. Storm Step Two™ - Polish lightly for 15 seconds each side.

Storm recommends using the suggested cleaner/polish daily. Storm also recommends touching up the surface with only the final step every 20 games and resurfacing completely every 30-50 games.



Use Reacta Shine™ Reactive Polish and Cleaner after every session.