

# Victory Road™



**COVERSTOCK:** R2S™ Pearl Reactive  
**WEIGHT BLOCK:** Inverted Fe<sup>3</sup> Technology™  
**FACTORY FINISH:** 1500-grit Polish  
**BALL COLOR:** Amethyst Pearl/Grey Pearl  
**DUROMETER:** 74-76 Rex D-scale  
**FLARE POTENTIAL:** 5" - 6" (High)  
**FRAGRANCE:** Warm Maple Syrup  
**WEIGHTS:** 12-16 lbs.

Lbs.	RG	Diff.
16	2.53	0.055
15	2.56	0.052
14	2.60	0.050
13	2.59	0.045
12	2.65	0.035

## Resurfacing to a 1500-grit Polished Factory Finish

Resurface to the original factory finish using a ball spinner.

1. 500-grit Abralon® - Sand for 30 seconds on all four sides with firm pressure.
2. 1000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
3. 2000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
4. 4000-grit Abralon® - Sand for 20 seconds on all four sides with light pressure.
5. Storm Step Two™ - Polish lightly for 15 seconds each side.

Storm recommends using the suggested cleaner/polish daily. Storm also recommends touching up the surface with only the final step every 20 games and resurfacing completely every 30-50 games.



Use Reacta Shine™ Reactive Polish and Cleaner after every session.